





With this handset your PC becomes a highly effective telephone.

Your constant companion – with a crystal clear sound even on the move

The USB handset Plathosys CT 140 PRO is the ideal version for all users who like to phone with a handset. Whether in the office or on the move, the handset appeals through its ease of use and can be used everywhere thanks to its straightforward installation via Plug & Play.

The wideband audio performance of the CT 140 PRO provides top voice quality and a natural sound when used with PC telephony. Thanks to the assistance of the standard Hearing-Aid-Compatibility (HAC), the CT 140 PRO allows those with hearing aids to use the latest communication technology in an age of Unified Communications.

Through the HID standard (Human Interface Device) the CT 140 PRO automatically links into every PC environment. Our development team will be pleased to provide support in customising your individual requirements and in integrating the Plathosys CT 140 PRO through API programming.



Features of the Plathosys CT 140 PRO

- Plug&play installation
- Elegant and attractive design
- Ring tone signal via loudspeaker in the handset
- Voice quality earpiece and microphone: Frequency range 100 Hz to 7.500 Hz according to ETSI ES 202 739 (wideband audio quality)
- Acoustic Shock Protection according to ETSI EG 202518
- Hook on/-off-function *
- Echo cancellation
- Hearing Aid Compatibility (HAC) according to FCC Part 68.316 and 68.317
- API-software available for the development of customers' specific applications
- EU-conformity to EU directive 1995/5/EG (R&TTE directive)/CE label



Technical Data

- Power supply (USB: 5V, max. 100mA)
- USB 1.1, 2.0 & 3.0
- USB connecting coiled cable 1,10 m (optional USB connecting plain cable 1,50 m)
- The system is addressable for 32 Bit and 64 Bit

Scope of delivery

- USB handset with coiled cable (plain cable on demand)
- Desk support
- Operating instructions

Material description

 Sturdy casing made of flame retardant plastic PC-ABS (Norm UL 94)

System requirements

- MS Windows
 XP / 2000 / Vista
- MS Windows 7 / 8.1
- Standard-USB Port (1.1. or higher)

Part No.

103743

